

HIMIWAY ZEBRA Premium All-terrain Electric Fat Bike



Frame | 6061 Aluminum frame

Headset | Neco H156EM 28.6*44-56*30

Fork | TRAMA FAT34-PLS-26" 100mm travel 15*135mm thru axle

Shock | Alloy front suspension fork with lockout and adjustment

Front Wheel | Rim: MD-147 26*4.0"*36H*12G A/V | Spoke: 12G 255/256L stainless (304M) | Hub: MB015-92 M9*12G*135*145W

Rear Wheel | Rim: MD-147 26*4.0"*36H*12G A/V | Spoke: 12G 256/257L stainless (304M) | Hub: GSMB019R-190F-GM14

Tires | Kenda 26*4.0

Battery | Samsung/LG 48V 20Ah

Motor | 500W mid-drive motor

Display | KD718-P LCD display with Type-c charger

Throttle | Thumb throttle

Sensors | Torque sensor, Shifting sensor, Speed sensor, Brake sensor

Crankset Crankarm: Prowheel 170mm / Chain ring: 44T BCD104
Freewheel Shimano CS-HG201-9 11-36T
Chain KMC E9 EPT 124L
Groupset Shimano altus M2000 9 speed
Front Brake Tektro HD-E350 hydraulic brake
Rear Brake Tektro HD-E350 hydraulic brake
Rotors Tektro TR180-52 F:180mm R:180mm
Range 60-80 miles
Controller 48V/22A
Charger US standard 3.0 A smart charger
Rider Height 5'1" ~ 6'5"
Weight 79 lb. (with battery)
Max Payload Capacity 400 lb.
A " Total Length 78.7 inches
B " Handlebar Height 47 inches
C " Handlebar Length 28 inches
D " Wheelbase 49.2 inches
E " Wheel Diameter 28.7 inches
F " Minimum Seat Height 20.9 inches
G " Maximum Seat Height 31.4 inches
H " Chain Stay Length 19 inches
I " Frame Stack 24.6 inches
J " Frame Reach 17.8 inches
K " Effective Top Tube Length 24.4 inches
L " Head Tube Length 5.5 inches

M 40" Head Angle | 65°

N 40" Standover Height | ST 22.4 inches / SO 31.1 inches